


DuraSystem® Extension set # WD6012000000

| < 230 mm > |



Extension set	Dimension	Weight	Order number
Suitable for increased installation height			
Colors			
00 White Alpin			
Variant			
		1.730 kg	WD6012000000
Installation accessories			
Installation element dry installation for WC Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards	500 x 155 mm	14.2 kg	WD1011
Installation element dry installation for WC Odour extraction, Fan activation: Manual, 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards	500 x 155 mm	17.5 kg	WD1012
Installation element dry installation for WC Hygienic flush, 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Electronic, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards	500 x 155 mm	16 kg	WD1013

DuraSystem® Extension set # WD6012000000

| < 230 mm > |

<p>Installation element dry installation for WC Odour extraction, Fan activation: Automatic, Manual, At the touch of a button, Touchless, Hygienic flush, 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Electronic, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	17.5 kg	WD1014
<p>Installation element dry installation for WC Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	14 kg	WD1016
<p>Installation element dry installation for WC Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	13.5 kg	WD1017
<p>Installation element dry installation for WC Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	15 kg	WD1018
<p>Installation element dry installation for WC Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	14.5 kg	WD1019
<p>Installation element dry installation for WC Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards</p>	500 x 155 mm	16 kg	WD1020
<p>Installation element for washbasin Standard Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Material of cross bars: Metal, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. threaded rods M10, Incl. HT outlet bend DN 50/40, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2</p>	500 x 170 mm	10.5 kg	WD2004

DuraSystem® Extension set # WD6012000000

| < 230 mm > |

<p>Installation element for washbasin special Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Material of cross bars: Wood, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. HT outlet bend DN 50/40, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2, Incl. hanger bolts M10</p>	500 x 170 mm	12.5 kg	WD2005
<p>Installation element for washbasin For wall faucet, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Material of cross bars: Wood, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. HT outlet bend DN 50/40, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2, Incl. hanger bolts M10</p>	500 x 170 mm	12.9 kg	WD2006
<p>Installation element for urinal Standard Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Material of cross bars: Wood, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. HT- outlet bend DN 50, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2</p>	500 x 170 mm	11 kg	WD3003
<p>Installation element for urinal Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Flush operation: Mechanical, Electronic, Flush operation position: Front, Material of cross bars: Wood, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. HT- outlet bend DN 50, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2</p>	500 x 170 mm	12 kg	WD3004
<p>Installation element for bidet Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Height adjustable: 240 mm, Material of cross bars: Metal, Suitable for panelling with plasterboards, Meter marking, Center marker, Height adjustable cross bars: 240 mm, Incl. drain pipe clamp DN 50, Incl. plinth legs, Incl. threaded rods M12, Incl. HT outlet bend DN 50/40, Incl. mounting accessories for single installation, Incl. mounting accessories for lightweight construction, Inkl. schallgedämmte Wandscheiben G1/2</p>	500 x 170 mm	11.89 kg	WD4002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.