

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|



Hand shower	Dimension	Weight	Order number
Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs			
Colors			
10 Chrome 46 Black Matt			
Variant			
Chrome/White, Ø 120 mm, Flow rate (3 bar): 14 l/min		0.240 kg	UV06500170..
Black Matt, Ø 120 mm, Flow rate (3 bar): 14 l/min		0.240 kg	UV06500170..
Chrome/White High Gloss, Ø 120 mm, Flow rate (3 bar): 9 l/min		0.240 kg	UV0650017C..
Black Matt, Ø 120 mm, Flow rate (3 bar): 9 l/min		0.230 kg	UV0650017C..
Suitable accessories			
Shower rail Hand shower holder: height adjustable	700 x 70 mm	0.32 kg	UV0600003
Shower rail 100 mm, Hand shower holder: height adjustable	100 x 70 mm	0.36 kg	UV0600004
wall outlet Round, Non-return valve: Individually, in the hose connection, Escutcheon shape: Round, Dimensions of water supply connection: DN 15	55 x 80 mm	0.27 kg	UV0630008
wall outlet Round, Non-return valve: Individually, in the hose connection, Escutcheon shape: Round, Dimensions of water supply connection: DN 15	55 x 102 mm	0.3 kg	UV0630009
wall outlet Square, Non-return valve: Individually, in the hose connection, Escutcheon shape: Square, Dimensions of water supply connection: DN 15	55 x 102 mm	0.3 kg	UV0630010
wall outlet Square, Non-return valve: Individually, in the hose connection, Escutcheon shape: Square, Dimensions of water supply connection: DN 15	55 x 80 mm	0.27 kg	UV0630011

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

| < 63 mm > |

Hand shower holder Plastic, Hand shower holder: Fixed, Mounting bracket shape: Conical	38 x 58 mm	0.04 kg	UV0620001
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1600 x 23 mm	0.34 kg	UV0610007
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1800 x 23 mm	0.37 kg	UV0610008
Suitable accessories for Chrome/White, Ø 120 mm, Flow rate (3 bar): 14 l/min			
Single lever shower mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection, Noise class: II	209 x 133 mm	1.4 kg	B14230000
Thermostatic shower mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Noise class: II	260 x 118 mm	1.8 kg	B14220000
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.8 kg	B14210010
Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Noise class: II	209 x 171 mm	1.6 kg	B15230000
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	B15210012
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	1.75 kg	B24210010
Single lever shower mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection, Noise class: II	179 x 137 mm	1.3 kg	B24230000
Thermostatic shower mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Noise class: II	260 x 113.5 mm	1.8 kg	B24220000

**Faucet Accessories Hand shower # UV06500170.. /
UV06500170.. / UV0650017C.. / UV0650017C..**

|< 63 mm >|

Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Noise class: II	182 x 170 mm	1.68 kg	B25230000
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	2.15 kg	B25210012
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	B14210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	2.15 kg	B15210018
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	2.15 kg	B24210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	2.12 kg	B25210018
Bathtub thermostat for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Shut-off and diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 94 mm	1.9 kg	C15200017
Bathtub thermostat for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Shut-off and diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 94 mm	1.9 kg	C15200018

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|

Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	2 kg	C15210018
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	2 kg	C15210017
Single lever shower mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 3 - 5 bar, Non-return valve in the hose connection, Flow rate (3 bar): 18,5 l/min	209 x 140 mm	1.33 kg	DE4230000
Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Flow rate (3 bar): 20,9 l/min	208 x 136 mm	1.41 kg	DE5230000
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	1.8 kg	DE4210010
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	2.1 kg	DE4210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	2.1 kg	DE5210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	2.2 kg	DE5210018
Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	1.8 kg	WT4210010

**Faucet Accessories Hand shower # UV06500170.. /
UV06500170.. / UV0650017C.. / UV0650017C..**

|< 63 mm >|

Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	2.2 kg	WT4210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	2.2 kg	WT5210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	2.2 kg	WT5210018
Single lever shower mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 10 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar	215 x 128 mm	0.9 kg	N14230000
Single lever bathtub mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 10 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Diverter automatically reverts from hand shower to bath spout when turned off	216 x 178 mm	1.3 kg	N15230000
Single lever mixer concealed set Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	115 x 83 mm	0.7 kg	N14210007
Single lever mixer concealed set Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	137 x 86 mm	1.4 kg	N15210008
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Security combination, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	TU5210018
Single lever shower mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 20 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection, Flow rate (3 bar): 17,1 l/min	210 x 114 mm	0.9 kg	A14230001

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|

Single lever bathtub mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 20 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Flow rate (3 bar): 15,5 l/min	210 x 166 mm	1.3 kg	A15230001
Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 73 mm	1.58 kg	CE4210008
Single lever shower mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	255 x 106 mm	1.68 kg	CE4230000
Single lever mixer concealed set Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round	125 x 72 mm	1.1 kg	CE4210007
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve	290 x 201 mm	1.96 kg	CE5230000
Single lever mixer concealed set Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 88 mm	1.17 kg	WA4210007
Single lever mixer concealed set Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, 130x130 mm, Including functional unit, Including trim parts	130 x 76 mm	1.08 kg	MH4210007
Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 89 mm	1.63 kg	WA4210008
Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, 125x171 mm, Including functional unit, Including trim parts	125 x 76 mm	1.61 kg	MH4210008
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.75 kg	N14210012

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|

Single lever shower mixer for concealed installation Number of outlets: 1, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.75 kg	N14210010
Single lever bathtub mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.75 kg	N15210012
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round	170 x 82 mm	1.66 kg	CE4210010
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round	170 x 82 mm	1.9 kg	CE4210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 82 mm	1.9 kg	CE5210012
Suitable accessories for Chrome/White, Ø 120 mm, Flow rate (3 bar): 14 l/min, Black Matt, Ø 120 mm, Flow rate (3 bar): 14 l/min			
Single lever shower mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 12,6 l/min, Noise class: II	272 x 103 mm	1.69 kg	C14230000
Thermostatic shower mixer for exposed installation Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection, Noise class: II	338 x 103 mm	2.13 kg	C14220000
Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 94 mm	1.8 kg	C14200013
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve, Noise class: II	314 x 190 mm	2.35 kg	C15230000
Bathtub thermostat for exposed installation Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Shut-off and diverter valve, Noise class: II	338 x 190 mm	2.55 kg	C15220000

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|

Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	1.9 kg	C15210012
Bathtub thermostat for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 94 mm	1.9 kg	C15200013
Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 94 mm	1.8 kg	C14200014
Thermostatic shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 94 mm	1.8 kg	C14200015
Thermostatic shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 94 mm	1.8 kg	C14200016
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	1.63 kg	C14210009
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	1.66 kg	C14210010
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	1.88 kg	C14210011
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	1.9 kg	C14210012

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|

Bathtub thermostat for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 94 mm	1.8 kg	C15200014
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	2.03 kg	C15210011
Single lever shower mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	280 x 113 mm	3.4 kg	TU4230000
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	1.8 kg	TU4210010
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	TU4210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 22,5 l/min, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	TU5210012
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve	313 x 191 mm	3.9 kg	TU5230000
Single lever shower mixer for exposed installation Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection	216 x 165 mm	1.66 kg	WA4230000
Bathtub thermostat for exposed installation Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 15 mm, Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Shut-off and diverter valve, Flow rate (3 bar): 18 l/min	303 x 223 mm	2.58 kg	WA5220000

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

|< 63 mm >|


Single lever bathtub mixer for exposed installation Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off	216 x 198 mm	1.76 kg	WA5230000
Single lever shower mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar	255 x 105 mm	2.07 kg	MH4230000
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve	286 x 213 mm	2.57 kg	MH5230000
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 82 mm	1.75 kg	MH4210010
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 82 mm	2.15 kg	MH4210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 82 mm	2.2 kg	MH5210012
Single lever bathtub mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Tub filler, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including trim parts	170 x 92 mm	2.2 kg	WA5210012
Single lever shower mixer for concealed installation Number of outlets: 1, Connection type for water supply connection: Basic Set, Ceramic cartridge, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 92 mm	1.8 kg	WA4210010
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 92 mm	2.2 kg	WA4210012
Thermostatic shower mixer for exposed installation 1000 Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection	303 x 113 mm	2.25 kg	TH4220000
Hand shower Spray mode: SilkRain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	260 x 130 mm	0.3 kg	UV0650018

Faucet Accessories Hand shower # UV06500170.. / UV06500170.. / UV0650017C.. / UV0650017C..

| < 63 mm > |

Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.



Faucet Accessories Hand shower # UV06500170.. /
UV06500170.. / UV0650017C.. / UV0650017C..

| < 63 mm > |

