

Faucet Accessories Showerhead # UV06620180.. /
UV06620180.. / UV06620180.. / UV06620180..

|< 58 mm >|



| Showerhead | Dimension | Weight | Order number |
|--|-------------|----------|--------------|
| Plastic, Showerhead angle adjustable, MinusFlow, Type of mounting: Ceiling mount, Wall installation, Spray mode: Rain | | | |
| Colors | | | |
| 04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel | | | |
| Variant | | | |
| Round, Diameter of showerhead: 250 mm, bronze Brushed | | 0.650 kg | UV06620180.. |
| Round, Diameter of showerhead: 250 mm, Chrome High Gloss | | 0.650 kg | UV06620180.. |
| Round, Diameter of showerhead: 250 mm, Gold Polished | | 0.650 kg | UV06620180.. |
| Round, Diameter of showerhead: 250 mm, Black Matt | | 0.650 kg | UV06620180.. |
| Round, Diameter of showerhead: 250 mm, Stainless steel Brushed | | 0.650 kg | UV06620180.. |
| Suitable accessories | | | |
| Shower arms Escutcheon shape: Round | 65 x 200 mm | 0.18 kg | UV0670025 |
| Shower arms Escutcheon shape: Round | 65 x 300 mm | 0.154 kg | UV0670026 |
| Shower arms Escutcheon shape: Round | 65 x 410 mm | 0.23 kg | UV0670028 |
| Suitable accessories for Round, Diameter of showerhead: 250 mm, Chrome High Gloss | | | |
| Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 86 mm | 2.2 kg | B14210012 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 87 mm | 2.15 kg | B24210012 |

Faucet Accessories Showerhead # UV06620180.. / UV06620180.. / UV06620180.. / UV06620180..

|< 58 mm >|

| | | | |
|--|--------------|---------|-----------|
| Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 80 mm | 2.1 kg | DE4210012 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 97 mm | 2.2 kg | WT4210012 |
| Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 100 x 100 mm | 0.15 kg | UV0660022 |
| Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 230 x 230 mm | 0.56 kg | UV0660017 |
| Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 250 x 250 mm | 0.65 kg | UV0660018 |
| Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 200 x 200 mm | 0.75 kg | UV0660019 |
| Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 300 x 300 mm | 1.3 kg | UV0660020 |
| Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain | 400 x 400 mm | 2.05 kg | UV0660021 |
| Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts | 125 x 73 mm | 1.58 kg | CE4210008 |
| Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts | 125 x 89 mm | 1.63 kg | WA4210008 |
| Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, 125x171 mm, Including functional unit, Including trim parts | 125 x 76 mm | 1.61 kg | MH4210008 |

Faucet Accessories Showerhead # UV06620180.. /
UV06620180.. / UV06620180.. / UV06620180.. / UV06620180..

| < 58 mm > |

| | | | |
|---|-------------|---------|-----------|
| Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 86 mm | 1.75 kg | N14210012 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round | 170 x 82 mm | 1.9 kg | CE4210012 |
| Suitable accessories for Round, Diameter of showerhead: 250 mm, Chrome High Gloss, Round, Diameter of showerhead: 250 mm, Black Matt | | | |
| Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts | 150 x 94 mm | 1.8 kg | C14200013 |
| Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 94 mm | 1.8 kg | C14200014 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts | 150 x 77 mm | 1.88 kg | C14210011 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts | 170 x 77 mm | 1.9 kg | C14210012 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts | 170 x 86 mm | 2.2 kg | TU4210012 |
| Shower arms Escutcheon shape: Round | 65 x 210 mm | 0.15 kg | UV0670027 |
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts | 150 x 82 mm | 2.15 kg | MH4210012 |

Faucet Accessories Showerhead # UV06620180.. /
UV06620180.. / UV06620180.. / UV06620180..

|< 58 mm >|

| | | | |
|---|-------------|--------|-----------|
| Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts | 170 x 92 mm | 2.2 kg | WA4210012 |
|---|-------------|--------|-----------|

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

